

迷你尺寸提供强大性能

Mini portable scanner with strong capability



集成灵活简单

Easy to use and integrate

- 独特精准的瞄准
- 内置 RS232 和 USB 接口
- 尺寸小-适应各种场合

- 多国语言条码信息直传
- 高速解码和高精度识读能力
- 简单易用-即插即用

- Accurate Aimer
- Miniature- easy to integrate
- Build in RS232 and USB interface
- High speed, Omni directional scanning
- Read all mainstream 1D/2D barcodes
- Multiple language barcode message transfer

Physical Characteristics		
尺寸Engine w/o Decode board:	70mm x 23mm x 50mm	
重量Weight:	50g	
电压Voltage:	5VDC	
电流Current:	400mA	
Performance Characteristics		
传感器像素Image(Pixels):	640 pixels(H) x 480 pixel(V)	
光源Light Source:	Aiming: 617 nm LED; illumination: 6500K LED	
视场角Field of View:	40°(H) x 26°(V)	
旋转倾斜偏转Roll/Pitch/Yaw:	360°, ±65°, ±60°	
打印对比度Print Contrast:	25% minimum reflective difference	
运动容差Motion Tolerances:	up to 25 in. (63.5cm) per second	
接口支持Interfaces Supported:	USB, RS232	
Symbology Decode Capability		
一维条码/1-D	UPC, EAN, Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Codabar Interleaved 2 of 5, Mis Plessey, GSI DataBar, China Postal, Korean Postal , etc	
二维条码/2-D	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.	
User Environment		
工作温度Operating Temperature:	0°C to 50°C	
存储温度Storage Temperature:	-40°C to 70°C	
湿度Humidity:	0% to 95% relative humidity, non-condensing	
抗震动Shock Specifications	Designed to withstand 1.5m(5') drops	
环境光免疫Ambient Light Immunity:	100,000 Lux	
Decode Ranges		
Symbol & Density	HD Focus	SR Focus
Code 39 (5 mil)	35mm - 120mm	60mm - 150mm
100%upca (13 mil)	38mm - 200mm	45mm - 380mm
Code 39 (20 mil)	38mm - 250mm	45mm - 400mm
PDF 417 (6.8 mil)	35mm - 125mm	40mm - 200mm
Data Matrix (10 mil)	35mm - 140mm	40mm - 120mm
QR Code (20 mil)	40mm - 180mm	40mm - 380mm
Resolution 1D Code 39	2.8mil (0.071mm)	4.8mil (0.122mm)
Resolution 2D Data Matrix	4.8mil (0.122mm)	6.6mil (0.168mm)
Performance may be impacted by bar code quality and environmental conditions		
   		