

SuperLead

苏州斯普锐智能系统有限公司

6200

高端固定式扫码器

Fixed Mount On Screen 2D Barcode Reader

工业等级金属外壳
Industrial-grade Metal Casing



集成灵活简单
Easy to Integrate

- 物体自感应
- 尺寸小-集成容易
- 高速，全方位的条码捕捉获取
- 全面读取所有主流一维、二维码
- Object auto sense
- Industrial leading scan platform
- High speed, Omni directional scanning
- Read all mainstream 1D/2D barcodes
- 多国语言条码信息直传
- 独特的精准瞄准
- 支持RS232接口和USB接口
- 读取纸张、移动电话及电脑显示器上的任何条码
- Multiple language barcode message transfer
- Miniature - easy to integrate
- Support RS232 and USB interface
- Read barcode off cell phone screens

Physical Characteristics				
尺寸Dimensions:	35mm x 47mm x 26mm			
重量Weight:	70g			
电压Voltage\ 电流Current:	5 VDC +/-10% @ 500 mA			
Performance Characteristics				
传感器像素Image (Pixels):	640 pixels (H)x 480 pixels (V)			
光源Light Source:	Aiming : 530 nm LED; illumination : 617 nm LED			
视场角Field of View:	6200-CC/6200-HD : 40.5° (H) x 31° (V); 6200-XHD : 22.6° (H) x 17° (V)			
旋转倾斜偏转Roll / Pitch / Yaw:	360°, ±65°, ±60°			
打印对比度Print Contrast:	25% minimum reflective difference			
接口支持Interfaces Supported:	USB, RS232			
运动容差Motion Tolerances	up to 6.2 m/sec (Code 39 20mil)			
Symbology Decode Capability				
一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.			
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.			
User Environment				
工作温度Operating Temperature:	-30°C to 60°C			
存储温度Storage Temperature:	-40°C to 70°C			
湿度Humidity:	0% to 95% relative humidity, non-condensing			
抗震性Shock Specifications:	Designed to withstand 0.5m drops			
环境光免疫Ambient Light Immunity:	0-100,000 Lux.			
环境密封等级Environmental Sealing:	IP42			
Decode Ranges				
		6200-CC	6200-HD	6200-XHD
1D	Code 39 (3mil)	-	30mm - 61 mm	37mm - 82mm
	Code 128 (3mil)	-	32mm - 60 mm	36mm - 83mm
	Code 128 (4mil)	45mm - 97mm	20mm - 105mm	45mm - 104mm
	Code 39 (5mil)	41mm - 113mm	24mm - 107mm	49mm - 112mm
2D	DM (4mil)	-	-	34mm - 91mm
	DM (7mil)	39mm - 65mm	21mm - 64mm	28mm - 121mm
	DM (10mil)	21mm - 105mm	13mm - 109mm	26mm - 127mm
	QR (10mil)	23mm - 127mm	15mm - 117mm	26mm - 121mm
Performance may be impacted by bar code quality and environmental conditions				
   				