

SuperLead

苏州斯普锐智能系统有限公司

6300

高端固定式扫码器

Fixed Mount On Screen 2D Barcode Reader

工业等级金属外壳
Industrial-grade Metal Casing



集成灵活简单
Easy to Integrate

- 物体自感应
- 尺寸小-集成容易
- 高速，全方位的条码捕捉获取
- 全面读取所有主流一维、二维码
- Object auto sense
- Industrial leading scan platform
- High speed, Omni directional scanning
- Read all mainstream 1D/2D barcodes
- 多国语言条码信息直传
- 独特的精准瞄准
- 支持RS232接口和USB接口
- 读取纸张、移动电话及电脑显示器上的任何条码
- Multiple language barcode message transfer
- Miniature - easy to integrate
- Support RS232 and USB interface
- Read barcode off cell phone screens

Physical Characteristics

尺寸Dimensions:	56mm x 47mm x 26mm
重量Weight:	92.5g
电压Voltage\ 电流Current:	5 VDC +/-10% @ 500 mA

Performance Characteristics

传感器像素Image (Pixels):	752 pixels (H)x 480 pixels (V)
光源Light Source:	Aiming: 617 nm LED; illumination: 6500K LED
视场角Field of View:	38° (H) x 25° (V) (跟随镜头规格变化)
旋转倾斜偏转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	25% minimum reflective difference
接口支持Interfaces Supported:	USB, RS232
运动容差Motion Tolerances	up to 5 M per second

Symbology Decode Capability

一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.

User Environment

工作温度Operating Temperature:	-30°C to 60°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity, non-condensing
抗震性Shock Specifications:	Designed to withstand 0.5m drops
环境光免疫Ambient Light Immunity:	100.000 Lux.
环境密封等级Environmental Sealing:	IP42

Decode Ranges

Code 39 (5mil)	50mm-110mm (跟随镜头规格变化)
100%upca (13mil)	40mm-300mm (跟随镜头规格变化)
1D Minimal Resolution	2mil

Performance may be impacted by bar code quality and environmental conditions

