

# 7190

## 扫码支付应用



专业手机读码器

Professional Mobile Phone Reader

大视野

Large Field of View



可以旋转90°，变成两种角度读码。

应用场景：便利店、快餐店、小微商店、

Physical Characteristics	
尺寸Dimensions:	115mm x 115x 105mm
重量Weight:	305g
电压Voltage:	5 VDC
工作电流Working Current:	300mA
待机电流Standby Current:	100mA
峰值电流Peak Current:	350mA
Performance Characteristics	
传感器像素Image (Pixels):	640 pixels (H)x 480 pixels (V)
光源Light Source:	Illumination:6500K LED
视场角Field of View:	40.5° (H) x 31° (V)
旋转倾斜偏转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	20% minimum reflective difference
接口支持Interfaces Supported:	USB, RS232
运动容差Motion Tolerance s:	>2m/s
Symbology Decode Capability	
一维条码/1-D:	UPC, EAN, Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Codabar Interleaved 2 of 5, Mis Plessey, GSI DataBar, China Postal, Korean Postal , etc
二维条码/2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec Hanxin, etc.
条码精度Minimum Resolution:	≥3.9 mil
User Environment	
工作温度Operating Temperature:	-20°C to 50°C
存储温度Storage Temperature:	-30°C to 80°C
湿度Humidity:	0% to 95% relative humidity,non-condensing
抗震性Shock Specifications:	Designed to withstand 1.5m(5' ) drops
环境光免疫Ambient Light Immunity:	0-100,000 Lux.
Decode Ranges	
6.88 mil (PDF417)	0mm-50mm
13 mil (UPCA)	5mm-110mm
20 mil (QR)	0mm-100mm
Performance may be impacted by bar code quality and environmental conditions	
   	