



大视野

Large Field of View

高端、大气
High-performance



- 物体自感应
- 内置RS232和USB接口
- Object self induction
- Build in RS232 and USB interface
- 超大扫描窗口
- 3种工作模式（普通模式，手机屏模式，以及快速移动模式）
- Super large reading window
- 3 working modes (normal mode, mobile phone screen mode and fast moving mode)

Physical Characteristics	
尺寸Dimensions:	105mmX146mmX70mm
重量Weight:	418g
电压Voltage:	5 VDC
电流Current:	500mA (Operating)
Performance Characteristics	
光源Light Source:	illumination: 5600K LED
市场角Field of View:	40° (H) x 25° (V)
偏转/倾斜/旋转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	20% minimum reflective difference
Symbology Decode Capability	
一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.
条码精度Minimum Resolution	5 mil Code39
接口支持Interfaces Supported:	USB, RS232
User Environment	
工作温度Operating Temperature:	32° to 122° F / 0° to 50° C
存储温度Storage Temperature:	-40° to 158° F / -40° to 70° C
湿度Humidity:	5% to 95%, non-condensing
抗震动Drop/Shock Specifications:	Withstands 10Gs 0.06" double amp
环境光免疫Ambient Light Immunity:	Immune to indoor lighting up to 1600 Lux. Immune to sunlight up to 86,000 Lux.
Decode Ranges	
5 mil (Code 39)	0mm-40mm
13 mil (100%Upca)	0mm-200mm
Performance may be impacted by bar code quality and environmental conditions	
   	