

安装方式简单灵活
Simple and Flexible Installation



功能强大
Powerful



- 物体自感应
- 尺寸小-集成容易
- 高速，全方位的条码捕捉获取
- 全面读取所有主流一维、二维码
- Object auto sense
- Industrial leading scan platform
- High speed, Omni directional scanning
- Read all mainstream 1D/2D barcodes
- 多国语言条码信息直传
- 独特的精准瞄准
- 支持RS232接口和USB接口
- 读取纸张、移动电话及电脑显示器上的任何条码
- Multiple language barcode message transfer
- Miniature - easy to integrate
- Support RS232 and USB interface
- Read barcode off cell phone screens

Physical Characteristics

尺寸Dimensions:	90mm x 49mm x 16mm
重量Weight:	49g
电压Voltage\ 电流Current:	5 VDC +/-10% @ 400 mA

Performance Characteristics

传感器像素Image (Pixels):	640 pixels (H)x 480 pixels (V)
处理器MCU:	飞思卡尔 Freescale 400MHz
感光芯片Sensor:	Hynix VGA
光源Light Source:	Aiming: 617 nm LED; illumination: 6500K LED
视场角Field of View:	45° (H) x 35° (V)
旋转倾斜偏转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	25% minimum reflective difference
接口支持Interfaces Supported:	USB, RS232
运动容差Motion Tolerances	Up to 15 cm per second

Symbology Decode Capability

一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.

User Environment

工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity, non-condensing
环境光免疫Ambient Light Immunity:	100.000 Lux.

Decode Ranges

Code 69 (5 mil)	60mm-100mm
100%upca (13 mil)	40mm-260mm
1D Minimal Resolution	4mil

Performance may be impacted by bar code quality and environmental conditions

